

**DECLARATION OF PERFORMANCE**  
**DoP N°4 LAMCO HPL COMPACT RE STD**

1. Unique identification code of the product-type: **LAMCO HPL COMPACT RE STD**
2. Intended uses: **HPL Laminate used as wall and ceiling external finishes**
3. Manufacturer: **LAMICOLOR S.p.A, Via Roma 23 - 12030 Caramagna P.te (CN) – ITALY**
4. Authorized representative: **N.A.**
5. System of AVCP (Assessment and Verification of Constancy of Performance): **System 3**
- 6a. Harmonized standard: **EN 438-7:2005**  
Notified body: **n° 0497: CSI S.p.A. - Viale Lombardia, 20 - 20021 BOLLATE – MI – ITALY**
- 6b. **N.A.**
7. Declared performances:

Essential characteristics	Performance	Harmonized technical specification
Reaction to fire	<b>C-s1,d0</b> thickness (mm) ≥ 6,0 mounted on metallic frame	EN 438-7:2005 section 4.2
Fire resistance	<b>NPD</b>	EN 438-7:2005 section 4.3
Water vapour permeability	<b>NPD</b>	EN 438-7:2005 section 4.4
Resistance to fixings	6 mm – 2000 N 8 mm – 3000 N ≥ 10 mm – 4000 N	EN 438-7:2005 section 4.5
Direct airborne sound insulation	<b>NPD</b>	EN 438-7:2005 section 4.6
Flexural tensile strenght (suspended ceilings)	<b>Pass</b>	EN 438-7:2005 section 4.8
Thermal resistance/conductivity	<b>NPD</b>	EN 438-7:2005 section 4.9
Thermal shock resistance	<b>Pass</b>	EN 438-7:2005 section 4.12
Durability	<b>Pass</b> - Resistance to wet conditions: ≥ rating 4 - Density: ≥ 1,35 g/cm <sup>3</sup>	EN 438-7:2005 section 4.13.2

8. Appropriate Technical Documentation and/or Specific Technical Documentation: **N.A.**

The performance of product identified above (point 1) is in conformity with the set of declared performances (point 7). This declaration of performance is issued, in accordance with Regulation (EU) N° 305/2011, under the sole responsibility of the manufacturer identified above (point 3).

Signed for and on behalf of the manufacturer by:

  
**Roberto Gandino**  
 Chief Executive Officer

**Caramagna P.te: 17/07/2019**